NKØE's AT Sprint II Quick Reference

Power-up Message

ATS X — X=2: 20m 14.060 MHz, X=3: 30m 10.110 MHz, X=4: 40m 7.040 MHz, X=8: 80m 3.560 MHz

CW Speed

exits with DIT after 1 sec of no activity

MENU → S (release after "S") — ↑ or — faster — ↓ or • slower

Tell Frequency

MENU → F (release after "F") — Reports kHz: DDDrD

Tune Mode

exits with DIT after 10 sec of no activity

MENU → T (release after "T") — • or — to tune

Enter Frequency

tells frequency on exit

MENU → E (release after "E") — • — enter 4 digits — "DIT" okay, "?" re-enter — MENU to abort

Enunciation CW Speed

MENU → U (release after "U") — Sets enunciation speed to current paddle speed

Exit Menu

MENU → F (release after 2nd "F") — Release Menu button after second "F" to exit menu

NKØE's AT Sprint II Quick Reference

RIT

RIT MSG — Response: "R" RIT on, "DIT" RIT off

Record Message

MENU → M (release after "M") — • — (up to 63 chars) enter message — MENU when done

message plays back — MENU to store — or — RIT MSG to re-record

Play Message

RIT MSG hold 1 sec — — hold to pause — or — • tap to stop

Beacon Message

RIT MSG hold 1 sec — msg plays — — hold — • tap — — release — msg repeats at 3 sec intervals

Specifications

Voltage supply: 5.5 – 12 V DC
TX out: 5W @ 12V, 2.5W @ 9V, 900mW @ 5.5V
RX current: 25mA typical, no signal
Weight: 5.5 oz (8 oz with internal batteries)
RX bandwidth: 500 Hz
Sidetone frequency: 600 Hz