

Yaesu VX-8GR Trail Reference Card

By NKØE

|  |  |
|--|--|
| <p><b>Volume</b></p> <p>VOL → [MUTE] → [PTT]</p> <p>hold set</p>                                 | <p><b>VFO</b></p> <p>[MUTE] → [PTT] → [1 MHz] → [BAND] → [BAND]</p> <p>tune 1 MHz band up band down</p>  |
| <p><b>A/B Bands</b></p> <p>[A▲] [B▼] → [A▲] [B▼]</p> <p>Toggle TX on A/B Hold for mono A/B</p>   | <p><b>Activate APRS</b></p> <ul style="list-style-type: none"> <li>- Select B band for TX, tune to 144.390 MHz</li> <li>- Turn on APRS modem to 1200 bps (menu 3)</li> <li>- Turn on GPS (menu 18)</li> <li>- Select GPS for MY POSITION (menu 23)</li> <li>- Choose beacon options (menus 12, 13, 14)</li> </ul> <p>Press [TX PO] to manually transmit a beacon</p> |
| <p><b>TX Power</b></p> <p>[MUTE] → [TX PO] → [PTT]</p> <p>L1 → L2 → L3 → HI TX at high power</p> | <p><b>Send APRS Message (Messages screen)</b></p> <p>[EMG R/H] → Enter → [HM/RV] → call/SSID → [MODE] → SPS SQ TYP</p> <p>EDIT mode</p> <p>→ Enter message or [A▲] [B▼] → [TX PO]</p> <p>Select message Send</p>   |
| <p><b>Mute RX-only Band</b></p> <p>[MUTE] → [7] → [PTT]</p> <p>set save</p>                      |  |
| <p><b>Squelch</b></p> <p>[MUTE] → [MONI T-CALL] → [PTT]</p> <p>set save</p>                      |  |

Yaesu VX-8GR Trail Reference Card

By NKØE

